

Avatar

HORSCH

Farming with passion

Avatar SD

Avatar SW

ROBUST, VERSATILE, PRECISE



Avatar

A NEW CHAPTER IN NO-TILL FARMING

HORSCH have never lost sight of the products that for 30 years have been forming its reputation: the first Seed-Extractors left a permanent impression. If you go back to the beginning of the company, Michael Horsch at that time built a machine that was suitable for no-till farming.

The arguments at that time: disturb the soil as little as possible, encourage biodiversity and, of course, in the context of decreasing prices, save costs. Due to the opening of the eastern markets in the Nineties there suddenly was a large market for no-till farming equipment. However the pto-shaft driven technology could not be used for the large fields in the East.

With the experiences from the no-till sector Michael Horsch developed tine-based no-till technology for the eastern markets that is successfully sold there today. In the recent past, HORSCH thought about developing no-till technology based on disc coulters. It is not just suitable for the Latin American markets to disturb the soil as little as possible.

But also in other regions, too, the single disc coulters technology is of great interest – especially in Europe with increasing requirements in the sector of catch crops sowing to the sowing of main crops in catch crops or in regions that are faced with resistant weeds. In parts of Great Britain, Germany and France the farmers depend on new sowing technologies with reduced soil movement – a clear task for the **Avatar**.

The disc coulters technology plays an important role in large parts of Russia, Kazakhstan and China.

Good reasons for HORSCH to design our own **Avatar** line.



SD (SINGLEDISC) COULTER

ROBUST, VERSATILE, PRECISE

Robust:

- Coulter pressure (up to 350 kg per coulter) is created via the well-proven rubber torsion system
 - No wear
 - No pivot points
 - Acts as a shock absorber (shocks from the coulter are not transferred to the machine)
- Long-life, maintenance-free bearings on all turning components for highest longevity and reliability
- Seed boot with carbide wear edges for increased service life and for safe scraping of earth from the seed disc even in most difficult conditions (cohesive soils, wet soils)

Versatile:

- Suitable for all sowing conditions
 - Direct seed
 - Mulch seed
 - Conventional tillage
 - In standing catch crops
 - Stony soils
 - Very heavy, clayey soils
- Closing wheels for safe closing of the seed furrow for all sowing conditions
 - Rubber or steel version for the adaption to the soil conditions
 - Standard angle adjustment of the closing wheel
 - Aggressive for no-till farming or on very heavy soils
 - Passive on cultivated or very light soils
- Press wheel in the row guarantees optimum firming of the seed at the bottom of the furrow
 - Safe emergence even in dry conditions
 - High reliability even in very wet conditions due to integrated parking position for the press wheel; the press wheel then is moved away from the working range

Precise:

- Stable depth control wheel for exact depth control of the coulter in changing or difficult soil conditions
- Wide depth control wheels in combination with a coulter pressure of max. 350 kg guarantee an exact placement of the seed in all sowing conditions
- The interaction of single disc coulter and seed shoe guarantees a safe opening of the furrow while at the same time harvest residues are removed from the furrow = optimum contact of seed and soil for quick and safe emergence



Steel closing wheel
Optional: steel or rubber closing wheel



Star roller steel –
excellent crumbling effect even in case
of a high amount of organic substance



Fine adjustment of the sowing depth




Uniformer Avatar



Press wheel in the seed furrow for
optimum seed-soil contact of the grain

Avatar 3/4/4 rigid/6/8 SD

COMPACT AND VERSATILE



First row

Seed 1: e. g. coarse seed placed deeply



Second row

Seed 2: small grains, placed shallowly, e. g. incl. slug pellets

Machine concept:


- Compact machine with working widths from 3 to 8 m
- 2-bar design with a row spacing of 16.7 cm and a clearance of 33.4 cm per row = reliability even with a lot of harvest residues resp. intensive catch crop population
- Large transport wheels to help reduce soil compaction even if the hopper is full
- Light basic machine for sowing after conventional tillage or mulch seed
- Possibility to mount additional weights to guarantee a safe forming of the furrow and firming of the seed with the SingleDisc coulter even in most difficult conditions
- Standard with mechanic half-width shut-off
- Optional: electric half-width shut-off to be controlled via the ISOBUS terminal or automatic with SectionControl activation

Versatile hopper system:


- Versatile with regard to the selection of the hopper system:
 - Single hopper and double hopper G & F (seed and fertiliser)
 - Avatar 3/4/4 rigid SD:
Single, double and triple hopper. Triple hopper with a partition of 60 : 10 : 30 for maximum flexibility, micro-granular unit in combination with single hopper
 - Avatar 6/8 SD:
Single hopper, double hopper. Micro-granular unit for single and double hopper, micro-granular unit with double hopper also available as an option with standard metering device (third component for fine seeds, slug pellets)
- Seed distribution:
 - Even distribution to the two seed rows
 - Optional for SD (depending on the equipment):
distribution of different seeds from the double hopper to the two seed rows (e. g. product 1 to seed row 1; product 2 + micro-granular to both seed rows)
- Optimum placement of seeds with different grain sizes by adaption of the placement depth to the requirements of the respective seed (large grains – deep, small grains shallow)




Sowing with the Avatar (functions depend on the equipment Avatar 3/4/4 rigid/6/8 SD)




Sowing of all rows



Sowing with double row spacing



Half-width shut-off from the cabin



Sowing of two different products (e. g. red = shallow, blue = deep)

Johannes von Keiser

“We have been using the **Avatar 6 SD** on our 750 hectare since 3 years and our experiences are only positive. The heavy soils with a short rotation wheat/barley/rape encourage the development of weeds and black grass. To fight the black grass problem, we carry out a shallow cultivation after the harvest to make the weeds emerge. Before sowing the fields they are treated with glyphosate.

Then we use the Avatar with the large single disc seed coulters. It moves only little soil while sowing and minimises further emergence of weed. We noticed that with reduced tillage we can drive earlier into the fields after rain and that biodiversity increases. Moreover, we attach great importance to efficiency to be able to sow at the correct time. With all these advantages the 6-metre Avatar pays off quickly.”



Optional: tyres 710/50–26.5 for maximum contact area



Double hopper 5 000 litre; partition 40 : 60




Triple hopper 3 800 litre, partition 60 : 10 : 30



2-point linkage

Avatar 12/18 SD

COMPACT AND EFFICIENT



Versatile hopper system for Avatar 12 SD
3 components are metered independently and place in a seed band

Concept of the machine:

- Compact, manoeuvrable machine
- HORSCH seed waggon concept for maximum efficiency
- Seed waggon Avatar 12 SD with a capacity of 5 800 litre; Avatar 18 SD: 8 500 litre, 50 : 50 partition seed / seed or seed / fertiliser
- Well-proven folding concept with compact transport dimensions; telescopic axle guarantees stability in the field, even in extremely hilly terrain and a maximum transport width of 3.00 m on the road
- Large tyres (Avatar 12 SD: 520/85 R 38, Avatar 18 SD: 520/85 R 42) at the seed waggon for maximum soil conservation and load-bearing capacity even in wet conditions
- Single-row design with SingleDisc coulter with row spacing of 25 cm

- Light-weight machine with integrated weight transfer and distribution to the coulter wings for homogeneous coulter pressure at all seed row to the very outside
- Low horsepower requirement due to little movement of soil
- Standard: mechanical half-width shut-off
- Optional: electric half-width shut-off to be controlled via the ISOBUS terminal or automatic with SectionControl activation (incl. micro-granular unit)

Versatile hopper system:

- Double hopper with optional micro-granular unit (only for Avatar 12 SD)
- Independent metering of up to 3 components (no de-mixing of seeds, exact metering seeds with different grain sizes)



Low Disturbance



Micro-granular unit Avatar 12 SD: 300 litre



Standard telescopic axle
Compact transport width; reduction of the track pressure behind the tractor track



Compact in transport;
large working width in the field



Hydraulic weight transfer from the seed waggon to the coulter frame:
Regularly high coulter pressure over the whole working width.



Large tyres on the seed waggon
Avatar 18 SD: 520/85 R 42



Jean Paul Kihm about the history of the project:

“During a meeting with Michael Horsch we talked about the problems on our farm. For quite some years already we are been having problems with the efficiency of plant protection agents with regard to black grass and ryegrass. Because of our problematic conditions we are forced to work with very short rotations wheat /barley /rape and a lot of winter crops, thus encouraging the development of weeds.

At the same time we were facing a second problem: A drinking water sample taken near some of our fields showed traces of plant protection agent residues. As a consequence the authorities told us to change our cultivation method. Based on these two problems – the increase of resistances and the demand to reduce our treatment frequency, we had to find a method to limit the emergence of weeds – and all that without any

additional plant protection measures. According to Michael Horsch a lot of farmers in Great Britain were facing the same problems. This is why we started to think about a seed drill that moves little soil and that leaves enough space to maybe carry out a mechanical measure later. It was to penetrate the soil in an optimum way and adapt perfectly to the terrain.

The basic idea of the Avatar was born. “The **Avatar 12 SD** was designed according to the ideas for French farmers, but it meets other requirements, too”, Jean Paul Kihm explains. “We wanted to continue to work efficiently and at the same time to reduce speed to guarantee a regular depth when placing the grains. The Avatar with twelve metre working width met these requirements to our entire satisfaction.”

Avatar SW

INNOVATIVE, EFFICIENT, WELL-PROVEN COMPONENTS

Concept of the machine:

- Maximum efficiency for large farms:
 - Working width 12 m
 - Seed waggon technology from the well-proven Pronto line
 - Designed for highest requirements and maximum efficiency during the season
- Seed waggon
 - Capacity of 12 000 litre for maximum efficiency
 - Hoppers 50 : 50 seed/seed or seed/fertiliser (application as G & F version, seed and fertiliser in one row)
- Low horsepower requirement due to reduced soil movement
- Manoeuvrable machine due to compact design
- Low horsepower requirement due to low machine weight



12 metre working width



Capacity of 12 000 litre with a 50 : 50 split hoppers



Solid monitoring sensors for seed and fertiliser



Compact design



2-bar coulter design for maximum clearance



Avatar SW on the road

ELEKTRONIKS INNOVATIVE AND DIGITAL SOLUTIONS



HORSCH Intelligence

The future machines think actively and HORSCH Intelligence makes it possible. With intelligent software and electronic solutions HORSCH seed drills work even more efficiently and help you to save both money and increase confidence.

HORSCH seed drill are always equipped with the ISOBUS standard. This does not only mean that every HORSCH machine can be controlled with any ISOBUS terminal. Additionally, SectionControl, VariableRate as well as the TaskController for data processing is a standard equipment for every HORSCH seed drill.

SectionControl

ISOBUS SectionControl allows for switching off individual sections automatically via GPS. The current position is determined, thus at field boundaries, on the headlands, in case of overlaps or in predefined areas individual sections (half-widths) or the whole working width is shut-off automatically.

When using a HORSCH Touch 800/1200 Terminal you can additionally use the MultiControl function. This function independently switches on and off the application of fertiliser and seed. Without MultiControl either fertiliser or seed can be switched on and off at the right time.

Advantages of SectionControl:

- Saving seed and fertiliser as overlaps on the headlands and at field boundaries are reduced to a minimum.
- Constant working quality on the whole field
- Productivity increase under various conditions (day and night, fog)
- Reduced stress for the driver
- Protection of the environment

VariableRate

ISOBUS VariableRate allows for a site-specific application of seed and fertiliser. Thus, with an appropriate application card for every section within a field the optimum quantity of fertiliser and seed can be applied. When using a HORSCH Touch 800/1200 Terminals you can additionally use the MultiControl function. This function allows for independently varying the amount of fertiliser and seed. Without MultiControl the application rate of either fertiliser or seed can be varied.

Advantages of VariableRate:

- Saving of seed and fertiliser as only the necessary quantity is applied
- Regular emergence due to optimum number of grains/m²
- Simple and quick documentation
 - The different application rates are documented automatically.
 - Uncomplicated transmission to the acreage index
- Reduced stress for the driver
 - The optimum application rate is automatically used on the fields.
- Protection of the environment
 - Only the necessary amount of fertiliser is applied.

TaskController

The ISOBUS TaskController transfers data from the PC to the terminal in an uncomplicated way. It is also possible to transfer application rates, sown area and other data that were recorded while sowing from the terminal to the PC. This facilitates the administration of the acreage index. Via the integrated order management system orders can be created and executed.

Advantages of the TaskController:

- Uncomplicated data exchange
- Automatic documentation
- Structured working due to data management
- Simple administration of the acreage index
- Simple accounting and proof for contract services



HORSCH Terminal




Touch 1200 Terminal



Touch 800 Terminal




TaskController



WITHOUT SectionControl

WITH SectionControl



Type 1

Type 2

Type 3

Type 1

Type 3

VariableRate takes different types of soil into account.



Soil quality	Seed	Fertiliser
high	300 grains/m ²	2.8 dt/ha PK
medium high	270 grains/m ²	2.5 dt/ha PK
medium low	250 grains/m ²	2.3 dt/ha PK
low	220 grains/m ²	2.0 dt/ha PK

VariableRate
Seed OR fertiliser

VariableRate with MultiControl
Seed AND fertiliser

VariableRate allows for applying adapted quantities of fertiliser and seed on the basis of application cards.

TECHNICAL SPECIFICATIONS



HORSCH Avatar	3.16 SD	4.16 SD rigid	4.16 SD	6.16 SD	8.16 SD
Working width (m)	3.10	4.00	4.00	6.00	8.00
Transport width (m)	2.99	4.32	2.99	2.89	2.98
Transport height (m)	3.50	3.50	3.50	3.06	3.98
Length (m)	6.96	6.96	6.64	7.12/7.82	
Weight (kg)	3 620*	4 500*	4 800*	7 900**	8 500**
Seed hopper capacity single hopper (l)	2 800	2 800	2 800	3 500	3 500
Feed opening single hopper (m)	1.00x2.40	1.00x2.40	1.00x2.40	1.00x2.40	1.00x2.40
Filling height single hopper (m)	2.85	2.85	2.85	2.52	2.92
Seed hopper capacity double hopper (l)	3 800	3 800	3 800	5 000	5 000
Feed opening double hopper (m)	per 0.66x0.90	per 0.66x0.90	per 0.66x0.90	per 0.66x0.90	per 0.66x0.90
Filling height double hopper (m)	3.24	3.24	3.24	2.35	3.26
Feed opening triple hopper (m)	0.66x0.43	0.66x0.25	0.66x1.45	---	---
Seed hopper capacity triple hopper (l)	3 800 (30:10:60)	3 800 (30:10:60)	3 800 (30:10:60)	---	---
Filling height triple hopper (m)	2.95	2.95	2.95	---	---
Hopper capacity micro-granular unit (l)	200	200	200	200	280
Number of seed coulters	18	24	24	36	48
Coulter pressure seed coulters (kg)	350	350	350	350	350
Seed coulter Ø (cm)	48	48	48	48	48
Closing wheels Ø (cm)	33	33	33	33	33
Depth control wheels Ø (cm)	40	40	40	40	40
Row spacing (cm/inch)	16.70	16.70	16.70	16.70	16.70
Tyre size seed unit/waggon	550/55–22.5	550/55–22.5	550/55–22.5	600/55–26.5	600/55–26.5
Working speed (km/h)	6–15	6–15	6–15	6–15	6–15
Power demand (kW/HP) from	90/125	105/140	105/140	155/210	200/270
Double-acting control devices		1 (+1 incl. hydr. fan direct drive)		3	3
Depressurized return flow (max. 5 bar)	1	1	1	1	1
Oil quantity hydr. fan (l/min)	35–45	35–45	35–45	35–45	35–45
Lower link linkage	Cat. III and III/IV	Cat. III and III/IV	Cat. III and III/IV	Cat. III and III/IV	Cat. III and III/IV
Adj. drawbar linkage	Hitch Ø 46–58 mm	Hitch Ø 46–58 mm	Hitch Ø 46–58 mm	Hitch Ø 46–58 mm	Hitch Ø 46–58 mm
Ball-type linkage	K 80	K 80	K 80	K 80	K 80

* Weight of the machine with minimum equipment without additional weights at the front and at the rear (1 000 kg)
** Weights of the machines with minimum equipment without additional weights at the front and at the rear (1 400 kg)

HORSCH Avatar	12 SD	18 SD
Working width (m/ft)	12.00/40	18.00/60
Transport width (m)	2.98	3.00
Transport height (m)	3.80	4.00
Length (m)	8.31	9.51
Weight (kg)	11 240*	48 seed coulters: 13 700/ 72 seed coulters: 15 000*
Seed hopper capacity double hopper (l)	5 800 (50:50, per 2 900 l)	8 500 (50:50, per 4 250 l)
Feed opening double hopper (m)	per 0.66x0.94	per 0.66x1.70
Filling height double hopper (m)	2.80	3.10
Hopper capacity micro-granular unit (l)	300	---
Number of seed coulters	48 – row spacing 25 cm 40 – row spacing 12” 32 – row spacing 15”	72 – row spacing 25 cm 60 – row spacing 12” 48 – row spacing 15”
Coulter pressure seed coulters (kg)	350	350
Seed coulter Ø (cm)	48	48
Closing wheels Ø (cm)	33	33
Depth control wheels Ø (cm)	40	40
Row spacing (cm/inch)	25/15”/12”	25/12”/15”
Tyre size seed unit/waggon	520/85 R 38	520/85 R 42
Tyre size support wheels	15.0/55–17	550/60–22.5
Working speed (km/h)	6–15	6–15
Power demand (kW/HP) from	220/300	220/300
Double-acting control devices	3	3
Depressurized return flow (max. 5 bar)	1	1
Oil quantity hydr. fan (l/min)	35–45	35–45
Adj. drawbar linkage	Ring hitch Ø 55–73 mm	Ring hitch Ø 55–73 mm
Ball-type linkage	K 80	K 80

* Weights of the machines with minimum equipment

HORSCH Avatar	12 SW
Working width (m)	12.00
Transport width (m)	4.36
Transport height (m)	5.28
Length (m)	11.65
Weight (kg)*	19 160
Seed hopper capacity double hopper (l)	12 000 (50:50, per 6 000 l)
Feed opening double hopper (m)	per 0.99x0.72
Filling height double hopper (m)	3.34
Number of seed coulters	60
Coulter pressure seed coulters (kg)	350
Seed coulters Ø (cm)	48
Closing wheels Ø (cm)	33
Depth control wheels Ø (cm)	40
Row spacing (cm)	20
Tyre size seed waggon	650/65 R 38
Tyre size seed unit	400/60–15.5
Working speed (km/h)	6–15
Horsepower requirement (KW/hp) from	205/280
Double-acting control devices	3
Depressurized return flow (max. 5 bar)	1
Oil quantity hydr. fan (l/min)	60–80
Adj. drawbar linkage	Ring hitch Ø 55–73 mm
Ball-type linkage	K 80

* Weights of the machines in minimum equipment





horsch.com

Your distributor:

HORSCH

HORSCH Maschinen GmbH
Sitzenhof 1
92421 Schwandorf

Phone: +49 9431 7143-0
Fax: +49 9431 7143-9200
E-Mail: info@horsch.com